

# DisplayPort™/HDMI™ KVM Switch For Dual DisplayPort™ 4K 60Hz



## Product Name:

DisplayPort™/HDMI™ KVM Switch For Dual DisplayPort™ 4K 60Hz

## Product Series:

Video Splitter

## Product Code:

CSV-7210

## EAN code:

8719214472238

## UPC code:

841615102457

## Description:

The CSV-7210 is a high performance DisplayPort™ KVM (Keyboard Video and Mouse) switcher. It routes high definition videos up to 4096x2160 at 60Hz resolution and audio from any DisplayPort™ source to any HDMI™ or DisplayPort™ supported display. This DisplayPort™ KVM switcher not only has the key press switching function, but also has an intelligent function as well as hot pluggable function.

## Features:

- Support resolution up to 4Kx2K@60Hz
- Support RGB 4:4:4/ YCbCr 4:4:4/ YCbCr 4:2:2/ YCbCr 4:2:0
- Support KVM function
- Support a DisplayPort™ or HDMI™ display and a set of Keyboard and Mouse to control two PCs with DisplayPort™ ports
- **DisplayPort™**  
Support 8.1Gbps per channel (32.4Gbps all channels) bandwidth  
Support 16bit per channel (48bit all channels) deep color  
Support HDR
- **HDMI™**  
Support 6Gbps per channel (18Gbps all channels) bandwidth  
Support 12bit per channel (36bit all channels) deep color  
Support HDCP 2.2/1.4  
Support HDR
- Support infrared remote control function
- Support for switching LED indications

## Supported resolutions:

- Max Resolution: 3840\*2160@60Hz, 4096\*2160@60Hz

Connectors		Operating Frequency	
Console Connectors	USB 2.0-A x2(Back)	HDMI™ Bandwidth	18G
	HDMI™ Female x1(Back)	DisplayPort™ Bandwidth	32.4G
	DisplayPort™ Female x1 (Back)	Mechanical	
	3.5mm Stereo Jack (Green, 1 Front, 1 Back) x2	Material	Metal
	3.5mm Stereo Jack (Pink, 1 Front, 1 Back) x2	Size (L-W-H)	17.8 x7.5 x 2.6 cm/ 7.0 x 2.95 x 1.02"
KVM Connectors	USB Gen1-B x2 (Back)	Weight (Net)	370 gr / 13.05 4 oz
	DisplayPort™ Female x2(Back)	Environmental	
	3.5mm Stereo Jack(Green, Back) x2	Operating Temperature	0°C to 45°C
	3.5mm Stereo Jack(Pink, Back) x2	Operating Humidity	10% to 85 % RH (no condensation)
USB HUB Connectors	USB Gen1-A x2 (Front)	Storage Temperature	-10°C to +80°C
		Storage Humidity	5% to 90 % RH (no condensation)
Resolution		Power Requirement	
Max Resolution	3840*2160@60Hz	External Power Supply	DC 5V
	4096*2160@60Hz	Power Consumption	(Max) 12W

Please use one of our Extension/Adapter cables to connect to your devices: In case you need assistance to choose the correct cable, please visit our website [www.club-3d.com](http://www.club-3d.com) or feel free to mail us at [support@club-3d.com](mailto:support@club-3d.com) and it will be our pleasure to assist you.



## OS Support:

- Windows/Apple Mac OS

## In the box:

- CSV-7210 DisplayPort™ KVM Switch x1
- External Power Supply 5V 3A x1
- IR Remote Control x1
- IR Extender x1
- USB Type B Male to USB A Male cable x2
- QR Code for downloading the Quick Installation Guide(QIG)

## Available Interfaces

### Input:

- **PC 1:** DisplayPort™ + USB + Mic + Stereo Port
- **PC 2:** DisplayPort™ + USB + Mic + Stereo Port
- 3.5mm Mic Input port
- DC 5V - Power Supply Unit

### Output:

- 1x HDMI™ Female
- 1x DisplayPort™ Female
- 1x MIC
- 1x Stereo Jack
- 1x USB Mouse connection
- 1x USB Keyboard connection
- 3.5mm Stereo port

## Other info:

- Box size: 23 x 18 x 5.5 cm / 9.05 x 7.08 x 2.56"
- Device size: 17.8 x7.5 x 2.6 cm/ 7.0 x 2.95 x 1.02"
- Box Weight: 145 gr / 5.11 oz
- Device Weight: 370 gr / 13.05 oz
- USB Type B Male cable Weight: 54 gr / 1.91 oz - 2x 108 gr / 3.81 oz
- IR Remote Control incl. battery Weight: 16 gr / 0.57 oz
- IR Extender Weight: 33 gr / 1.16 oz
- Power Adapter Weight: 107 gr / 3.77 oz
- Total Weight: 779 gr / x 27.48 oz
- Meets ROHS, FCC, and CE EMI requirements

## Input:



## Output:

